Project Reference No. 19-0424 REBIDDING

P.R No. 2019-0818

Standard Form Number: SF-GOOD-58

Revised on: May 24, 2004

Standard Form Title: Purchase Order

PURCHASE ORDER GOVERNOR'S OFFICE

Agency / Requisitioning Office

		Agency / Hogarita		P.O. NO.	2020-161
Supplier		B & J COMPUTER AND ELECTRONICS SERVICES	D.O. No.		
Address		0045-Saint Jude Bldg., Gallares St., Poblacion II, Tagbilaran City	Date: March 9, 2020		
\		Tagonal art every	Mode of		
E-mail Address		411-0687	Procurement : Bidding		
Telephone No.		118-664-518-000			
TIN Gentlemen/N		ic.			
Gentlemen/IV	uesuame	nis Office the following articles subject to the terms and	conditions cor	tained herein:	
Place of Delivery :		GOVERNOR'S OFFICE	Delivery Term:		
Address :		New Capitol Site, TAGBILARAN CITY	back hereof.		
Date of Delivery :		within 15 days upon receipt of NTP	Payment Term	yment Term upon completion of delivery	
Warranty P		1 year		T	AMOUNT
ITEM	UNIT	DESCRIPTION	QTY.	UNIT COST	AMOUNT 56,000.00
1	UNIT	DSLR CAMERA(Body Only) - NIKON	1	56,000.00	56,000.00
2		with Accessories	}		
		24.3MP FX-Format CMOS Sensor	1		
	<u> </u>	Expeed 3 Image Processor	1		
	1	3.2" 921k-Dot LCD Monitor		ļ	
		Full HD 1080p Video Recording at 30 fps			
		Multi-Cam 4800 39-Point AF Sensor			
		Native ISO 6400, Extended to ISO 25600			
		6 fps Shooting at Full Resolution			
	}	Built-in Flash with Commander Mode		31,360.00	31,360.0
	דומט	SPEEDLIGHT SB-910 - NIKON COMPATIBLE	1	31,500.00	
	1	Fully compatible with Nikon Creative Lighting System		\	
		Three illumination patterns(standard/even/center- weighted)with increased light distribution accuracy, are available to match every shooting environment.			
		Power Zoom Function Covers Wide 17-200mm(in FX Format) or 12-200mm(in DX Format) zoom ranges.			
		AF-assist illumination, compatible with multi-point AF System, Covers wide 17-135mm Focal Length Range.			
		New Menu Button Enables Quick Access to Custom Settir While improved LCD Panel GUI Enhances Operability.	ngs,		
		Durable and Heat -Resistant, Easy-to-use, Hard-Type Col Filtr	or		
		Hard-Type Color Filters (Flourescent or incandescent) included.			
		Automatically Detects Color Filter types and transmits fil information to camera for optimum white balance setting	iter ng.		
		Guide number: 34/111.5(m/ft.) at 35mm and 53/173.9(m/ft.) at 200mm(FX-Format, Standard			
		illumination pattern, ISO 100, 20°C/68°F).			