

			<p>Mount, Shockmount (via Integrated Hardware)</p> <ul style="list-style-type: none"> Dimensions: ϕ: 3.94 x L: 6.69" / ϕ: 100 x L: 169.93 mm <p>Weight: 3 oz / 85g</p>		
2	1	Pc	<p>SmartLav + Lavalier Condenser Microphone</p> <p>Specs:</p> <p>Microphone</p> <ul style="list-style-type: none"> Operating Principle: Pressure Gradient Diaphragm: 0.110" / 2.54mm Polar Pattern: Omnidirectional Orientation: End Address Circuitry: Solid- State (JFET) <p>Performance</p> <ul style="list-style-type: none"> Frequency: 60 Hz to 18 kHz Maximum SPL: 110 dB SPL Impedance: 3 Kilohms Sensitivity: -35dB Dynamic Range: 83dB Signal-to-Noise Ratio: 67 dB Equivalent Noise Level: 27 dB A-Weighted <p>Connectivity</p> <ul style="list-style-type: none"> Output Connectors (Analog): 1 x 1/8" / 3.5mm TRRS <p>Physical Info</p> <ul style="list-style-type: none"> Box Dimensions (LxWxH): 5.95 x 3.25 x 0.75" 	8,100.00	8,100.00
3	1	Pc	<p>Boompole with Bag</p> <p>Specs:</p> <ul style="list-style-type: none"> Weight: 940.00g <p>Dimensions: 3232.50mmH x 40.00mmW x 40.00mmD</p>	20,000	20,000.00
4	2	pcs	<p>LED Light Kit with V-Mount Battery Plate (Studio LED Light)</p> <p>Specs:</p> <p>Light Fixture</p> <ul style="list-style-type: none"> Beam Angle: 55° Color Temperature: 5500K Color Accuracy Standard: CRI 96 at 5500K TLCI 96 at 5500K CQS 95 at 5500K Cooling System: Fan / Passive Combo Dimming: Yes, 0 to 100% (Continuous) Display: None Housing Material: Aluminum Photometrics: 55° at 5500K: Fixture Dimensions: Overall: 11.7 x 8.5 x 13.6" / 298.4 x 215.6 x 344.5 mm 	70,000	140,000.00