

			5.6 Spatial resolution:3.6lp/mm 5.7 Pixel gray level : :14bit 5.8 Data output: wired/wireless; CPU:3.2GHz 6.2 Memory capacity : 4GB 6.3 Hard drive capacity : 500 GB 6.4 Resolution: 1280 x 1024 6.5 Display size : The 21inch color LCD capacitive touch screen, multi-touch 6.6 64 bit Windows operation system;		
			Patient registration: acquisition, find the patient data, to prepare for the photography 7.2 Radio graphic examination : setting system parameters, exposure photography and get the image 7.3 Images display, image analysis, processing and output 7.4 Data management: managing patient data, leading in, leading out , batch file, etc in accordance with		
			DICOM3.0 7.5 Configure calibration: the system components such as flat-panel detector, such as tube for automatic configuration and calibration 7.6 System diagnosis: monitoring system status, diagnosis of the system fault; Frame size 8.1.1 Width : 1070 mm 8.1.2 Length : : 2200 mm 8.1.3 Height : 2140 mm 8.2 Lathe bed size 8.2.1 Width : 710 mm 8.2.2 Length : : 1250 mm 8.2.3 Height : 500 mm 8.3 Size of the bed 8.3.1 Width : 820 mm 8.3.2 Length : : 2120 mm 8.4 Total weight (no detector) : 700kg 8.5 Bed bearing: 200kg 8.6 Support automatic exposure dose control function; The machine warranty 1 year 9.2 1 set of complete operation and maintenance manual 9.3 Provide site application and service training 9.4 Free service hot line		
			resolution:3.6lp/mm 5.7 Pixel gray level : :14bit 5.8 Data output: wired/wireless; CPU:3.2GHz 6.2 Memory capacity : 4GB 6.3 Hard drive capacity :		
			500 GB 6.4 Resolution: 1280 x 1024 6.5 Display size : The 21inch color LCD capacitive touch screen, multi-touch 6.6 64 bit Windows operation system; Patient registration: acquisition, find the patient data, to prepare for the photography 7.2 Radio graphic examination : setting system		
			parameters, exposure photography and get the image 7.3 Images display, image analysis, processing and output 7.4 Data management: managing patient data, leading in, leading out , batch file, etc in accordance with DICOM3.0 7.5 Configure calibration: the system components		
			such as flat-panel detector, such as tube for automatic configuration and calibration 7.6 System diagnosis: monitoring system status, diagnosis of the system fault; Frame size 8.1.1 Width : 1070 mm 8.1.2 Length : : 2200 mm 8.1.3 Height : 2140 mm 8.2 Lathe bed size 8.2.1 Width : 710 mm 8.2.2 Length : : 1250 mm 8.2.3 Height : 500 mm 8.3 Size of the bed 8.3.1 Width : 820 mm 8.3.2 Length : : 2120 mm 8.4 Total weight (no detector) : 700kg 8.5 Bed bearing: 200kg 8.6 Support automatic exposure dose control function;		
			The machine warranty 1 year 9.2 1 set of complete operation and maintenance manual 9.3 Provide site application and service training 9.4 Free service hot line		
3	3	unit	ECG Machine, 12 Leads with analyzer - NEWTECH OR CHINA	77,600.00	232,800.00
			- 12 lead resting ECG with standard ECG measurements Backlit VGA LCD screen		
			- Full Alphanumeric keyboard		
			- High resolution thermal print head		
			-Automatic and Manual Operation		
			-Storage for up to 50 ECGs		
			- 1 year warranty		
4	1	unit	Dental Chair with Accessories	277,420.00	277,420.00
			Fully adjustable:		
			: Multifunction Foot control		
			*adjustable tilting backrest		
			*adjustable seat cushion height		
			Patient chair		