

6	10	LOT	<p>SINGLE MINDER PULLEY (PRUSIK MINDING PULLEY).. Special side plates designed for use with a Prusik friction hitch in progress capture systems</p> <p>Large diameter sheave mounted on sealed ball bearings for excellent efficiency</p> <p>Accepts up to three carabiners to facilitate use</p> <p>Specifications</p> <p>Rope compatibility: 7 to 13 mm</p> <p>Sheave diameter: 51 mm</p> <p>Ball bearings: yes</p> <p>Efficiency: 97 %</p> <p>Maximum working load: 4 kN x 2 = 8 kN</p> <p>Weight: 295 g</p> <p>Certification(s): CE EN 12278, NFPA 1983 General Use</p>	7,164.00	P 71,640.00
7	4	LOT	<p>TANDEM PULLEY.. Aluminum sheaves mounted on self-lubricating bushings for efficiency</p> <p>Accepts up to three carabiners to facilitate use</p> <p>Specifications</p> <p>Rope compatibility: diameter: 13 mm or less</p> <p>Sheave diameter: 21 mm</p> <p>Ball bearings: no</p> <p>Efficiency: 71 %</p> <p>Maximum working load: 10 kN</p> <p>Weight: 195 g</p> <p>Certification(s): CE EN 12278</p>	4,709.25	P 18,837
8	4	LOT	<p>PAW RIGGING PLATE MEDIUM (YELLOW).. For easy organization of the workstation and setup of multi-anchor systems:</p> <ul style="list-style-type: none"> - 19 mm holes allow the locking sleeves of most carabiners to pass through, enabling the carabiner to be rotated - hole design allows ropes or slings to be threaded for direct connection. - main attachment hole accepts up to three carabiners - the odd number of attachment holes enables the system to be centered and balanced - up to three users can be connected at the same time <p>Durability:</p> <ul style="list-style-type: none"> - made of forged aluminum for an excellent strength-to-weight ratio - durable markings, thanks to the recessed area in the center of the plate <p>Material(s): aluminum</p> <p>Certification(s): CE, NFPA 1983 General Use</p>	4,910.50	P 19,642