

		38	62,500	2,375,000.00
3	<p>units</p> <p>Technical Specifications</p> <p>Overall Length: 2140mm</p> <p>Overall Width: 1750mm</p> <p>Overall Height: 960mm</p> <p>Weight without Engine: 98 kg</p> <p>Type of Main Clutch: Idler</p> <p>Type of Power Transmission System: Engine to drive shaft: Pulley and V Belts</p> <p>Drive Shaft to Axle: Chain and Sprocket</p> <p>Engine Pulley (Stub Pulley): Double Groove B-Section (76mm x 2B)</p> <p>Drive Shaft Pulley: Double Groove B-Section (305mm x 2B x 29mm)</p> <p>Axle: Type: Square end, Cross-Section: 22mm x 22mm, Overall length: 610mm</p> <p>Rotary Tilling Wheel:</p> <p>Overall Length: 480mm</p> <p>Overall Diameter: 355mm</p> <p>Engine:</p> <ul style="list-style-type: none"> Type: Air-Cooled, Four Stroke, single vertical cylinder Diesel Engine Bore x Stroke: 86 x 72 mm Exhaust System: Muffler Total Displacement volume: 418cc Engine weight: 44.5 kg Maximum rated power: 8.96 kW (12Hp) Continuous Power: 8.21 @3600rpm Starting System: Rope Recoil Type of Fuel Feed: Gravity Fuel used : Diesel Air cleaner: Oil Bath Type Lubricating system: Force- Feed type <p>Brush Cutter:</p> <ul style="list-style-type: none"> engine type: two-stroke, air cooled power: 2.2KW displacement: 52cc Fuel tank: 1200ml pole length: 1500mm pole type: nylon/metal Fuel: 2-cycle oil mix gasoline ratio=1:25 G.W/N.W: Engine: 4.0/5.5KG Shaft: 3.0/3.6KG 	106	4,700	498,200.00
4	<p>units</p> <p>Water Pump (3 inch) 6.5HP gasoline with Inflow hose 10 meters (3")</p> <p>Outflow hose 100 meters (3")</p> <p>Specifications:</p> <ul style="list-style-type: none"> Engine Model: recoil start 6.5hp gasoline engine Oil Alarm: without Air Cleaner: semi-dry Carburetor: Hongyu brand Camshaft: nylon Inlet & Outlet Pipe Diameter: 80mm (3") 	53	15,094.34	800,000.02