

Item No.	Quantity	Units of Issue	Item Description	Estimated Unit Cost	Estimated Cost
1	4	units	Bouyancy Control Device Specifications: • Size: XXS • New technologically advanced ResisteK™ material resists fading and abrasion. • Proprietary backpack with built in carrying handle. • Waistband is adjustable in the back • 1000 denier BCD with reinforced layer of material • Scooped octo-pocket on the top front of the right lobe • Large, easy-to-access utility pocket on each side of the wave. • 2 stainless steel flat D-rings. • Right shoulder pull dump with highly visible orange pull bob. • Lower rear dump flat valve with highly visible orange pull bob • Adjustable chest strap. • Detachable, double adjusting crotch strap with neoprene center • Tank band for a 30 cu. ft. cylinder (p/n 427056) • BCD color is combination of Black, Orange and Gray • Color coded by size with reference on the lower section • With certification that regulator was tested at depth 50msw with an air flow of 830 l/min at water temperature of 10°C.	21,599.76	86,399.04
2	3	set	Regulator (complete set) Specifications: AT20 Stage 3 sets Regulator Octopus and Termo Gauge Combo 2K SPG/MDI, with hose metric First Stage • UST Balanced diaphragm design; • 1 HP port and 4 MP ports available. Second Stage • Pneumatically-balanced second stage. • Integrated venturi control; comfo-bite mouthpiece. AT20 OCTO • Pneumatically-balanced second stage; • Diver has full control of the venturi; Made in UK Console Depth Gauge • Scale of 70 meters; Red marking: 3 to 6 meters • Phosphore Bronze C Bourdon tube; silicone oil filled Pressure Gauge • One piece brass body; copper Beryllium spiral wound • Polycarbonate transparent window • Graduation 400 BAR / 5000 PSI, full scale; luminous • Red zone from 0 to 50 BAR; standard Hose length 80 cm / 32" • Made in Italy Underwater Camera Specifications: • 16 megapixel IMX083 CMOS 1/2.3" image sensor • iCatch V50 DSP processor; 260K hi-res 2.4" TFT color LCD • 4K Ultra HD Video @ 30fps and 1080p HD video @ 120 fps (Super Slo-Mo) • Permanently sealed – No waterproof door or O-rings to maintain • Ultra-fast 0.1 second shutter response- Virtually no shutter lag	32,377.28	97,131.84
3	2	units	Underwater Camera Specifications: • 16 megapixel IMX083 CMOS 1/2.3" image sensor • iCatch V50 DSP processor; 260K hi-res 2.4" TFT color LCD • 4K Ultra HD Video @ 30fps and 1080p HD video @ 120 fps (Super Slo-Mo) • Permanently sealed – No waterproof door or O-rings to maintain • Ultra-fast 0.1 second shutter response- Virtually no shutter lag	33,415.20	66,830.40
Total					250,361.28

Purpose: **For use in the underwater monitoring and assessment in the Province**

Requested by:	Cash Availability:	Approved by:
Signature:		ATTY. ARTHUR C. YAP Governor
Printed Name: JOVENCIA B. GANUB, EnP.	EUSTAQUIO A. SOCORIN	By Authority of the Governor:
Designation: Head-BPEMO	Provincial Treasurer	ATTY. KATHYRIN FED. PIOQUINTO Provincial Administrator