

	<p>ISO Range: Video:100-3200(Auto), 100-6400(Manual) ;  Photo:100-3200(Auto), 100-12800(Manual)  Mechanical Shutter Speed: 8 - 1/2000 s  Electronic Shutter Speed: 8 - 1/8000 s  Max Image Size: 4864×3648 (4:3) ;  5472×3648 (3:2)</p> <p>Video Recording Modes: H.264, 4K : 3840×2160 30p  Photo Format: JPEG  Video Format: MOV  Supported File Systems: FAT32 (≤ 32 GB) ; exFAT (&gt; 32 GB)  Supported SD Cards: MicroSD, Max Capacity: 128 GB.  Class 10 or UHS-1 rating required Write speed≥15 MB/s  Operating Temperature Range : 32° to 104° F (0° to 40°C)</p> <p>Intelligent Flight Battery(PH4-5870mAh-15.2V)  Capacity: 5870 mAh  Voltage: 15.2 V  Battery Type: LiPo 4S  Energy: 89.2 Wh  Net Weight: 468 g  Charging Temperature Range: 14° to 104°F(-10° to 40°C)  Max charging Power: 160 W  Intelligent Battery Charging Hub(WCH2)  Input Voltage: 17.3 - 26.2 V  Output Voltage and Current: 8.7 V, 6 A ; 5 V, 2 A</p> <p>Operating Temperature: 41° to 104°F(5° to 40°C)  SDK Remote Controller  Operating Frequency: 2.400 GHz to 2.483 GHz (Europe, Japan, Korea), 5.725 GHz to 5.850 GHz (Other countries/regions)  EIRP: 2.4 GHz - CE / MIC / KCC: &lt; 20 dBm, 5.8 GHz - FCC / SRRC / NCC: &lt; 26 dBm  Max Transmission Distance: FCC / NCC: 4.3 mi (7 km); CE / MIC / KCC / SRRC: 3.1 mi (5 km); (Unobstructed, free of interference)  Built-in Battery: 6000 mAh LiPo 2S  Operating Current / Voltage: 1.2 A @ 7.4 V  Mobile Device Holder: Tablets and smartphones  Operating Temperature: 32° to 104° F (0° to 40° C)  GNSS  Single-Frequency, High-Sensitivity GNSS Module:  GPS+BeiDou+Galileo (Asia) ;  GPS+GLONASS+Galileo (other regions)</p>			
--	---	--	--	--