



Standard Form Number: SF - GOOD-58  
Revised on: May 24, 2004  
Standard Form Title: Purchase Order

Negotiated Canvass No. - PHO - 2022 - 259  
Purchase Request No. - PHO - 2022 - 324

**PURCHASE ORDER**

FRANCISCO DAGOHOY MUNICIPAL HOSPITAL, INABANGA, BOHOL  
Agency/Procuring Entity

Supplier :	<b>B&amp;J COMPUTER SALES AND ELECTRONIC SERVICES INC.</b>	D.O. No. :	P.O. # - PHO - 2022-383
Address :	<b>0409, Bantol St., Dampas District, Tagbilaran City</b>	Date :	December 19, 2022
Telephone No.:		Mode of Procurement :	Negotiated Canvass
TIN :			(2nd Failure of Bidding)

Gentlemen/Mesdames:

Please furnish this Office the following articles subject to the terms and conditions contained herein:

Place of Delivery:	<u>FRANCISCO DAGOHOY MUNICIPAL HOSPITAL, INABANGA, BOHOL</u>	Delivery Term: Please Read Terms & Conditions at the back hereof
Date of Delivery :	<u>THIRTY (30) DAYS UPON RECEIPT OF NOTICE TO PROCEED</u>	Payment Term: Progress Billing
Warranty Period:	<u>ONE (1) YEAR</u>	

Item No.	QTY	UNIT	DESCRIPTION OF SUPPLIES	UNIT COST	AMOUNT
1	1	UNIT	SOUND SYSTEM SET	33,900.00	33,900.00
			Speaker set		
			-Active subwoofer:15" subwoofer,4" Line array:2 x 300 watts max,		
			• Array Midrange:4" x 8pcs(voice coil size=1"), Array Tweeter:1" x 8pcs		
			• USB /SD/FM/ Bluetooth Connectivity		
			• Auxiliary in, Remote control		
			• 2mic Input		
			• Package includes: 2 pcs-6m Speaker Link Cable, 6 pcs-0.3 Array Link Cable, 2pcs-Assembly Bracket, 2 pcs-1.8m Tripod Stand		
			• AC Power:220V, 60Hz		
			Wireless Microphone		
			2 piece wireless microphone with charging function product features		
			• .50 channels freely selectable settings		
			• Effective Distance in Open Environment		
			• The Microcomputer controlled FLL phase-locked loop oscillation circuit has stable performance and convenient setting		
			• LED Digital Display Mode makes operation more intuitive		
			• Equipped with balance and unbalanced audio output, it can be connected to any product mixer and amplifier.		
			AUDIO MIXER		
			• 6 Channels Stereo Mixer-2XLR Input and 4 TRS Input (1/4 jack)		
			• Digital Delay-Delay System in Hi-fi will help acquire better echo effect.		
			• Gain Control/Peak Indicator		
			• Use Gain Control and peak led to control input signal and prevent distortion caused by overload.		
			• Tape Input-Connect with cassette to play		
			• Headphone Monitor		
			• Frequency Response input to stereo output: +0.5dB/-0.5dB(20Hz to 20kHz)		
			• Total Harmonic distortion input to stereo out: 0.01% @ + 8dBu(20Hz to 20kHz), Gain Knob: Min 0.003% @ +18dBu (1kHz), Gain Knob: Min		
			• Input channels : 6 channels : Mono(Mic/Line): 2 stereo(Line): 2		
			• Output Channels: Stereo out: 2, Phone: 1 Bus: Stereo: 1 Mono input channel		