

	MATERIALS AND SPECIFICATIONS:				
	REINFORCED CONCRETE COLUMN FOOTINGS, TIE BEAMS, WALL FOOTINGS, COLUMNS, ROOF BEAMS, STIFFENERS AND FLOOR SLAB ON FILL PLAIN CEMENT PLASTERED, 4" THICK CONCRETE HOLLOW BLOCKS MASONRY WALLS				
	ANGULAR BAR ROOF TRUSS MEMBERS AND FASCIA FRAMES, 1.5mm THICK C- PURLINS, PLAIN ROUND BAR SAG RODS AND SWAY BRACES, APPROPRIATELY PAINTED WITH METALS PRIMER AND 12MM THICK x 30CM WIDTH CEMENT FIBER FASCIA BOARD				
	PRE-PAINTED LONG SPAN GALVALUME CORRUGATED ROOFING INCLUDING ROOFING ACCESSORIES AND CONSUMMABLES				
	4.5MM CEMENT FIBER CEILING BOARD ON LIGHT METAL FRAMES AND 6MM THICK CEMENT FIBER BOARD ON METAL FRAMES FOR DOUBLE WALL DRY PARTITION				
	SOLID PANEL DOOR WITH WOODEN JAMB AND 6MM CLEAR GLASS ON ALUMINUM FRAMES SLIDING WINDOWS				
	GLOSS MASONRY PAINT FOR INTERIOR AND EXTERIOR CONCRETE AND MASONRY SURFACES AND FLAT PAINT FINISH FOR INTERIOR CEILING BOARD				
	PPR PIPES FOR PROCESSED WATER CONNECTIONS IN BUILDING	101210433	956		
	THHN STRANDED COPPER WIRE IN PVC ELECTRICAL CONDUIT EMBEDDED IN MASONRY WALLS OR				