

# PURCHASE REQUEST

## Province of Bohol

GO

Phm-0021 - 723

Department : GO

PR No. \_\_\_\_\_

SAI No. \_\_\_\_\_

Section : \_\_\_\_\_

ALOBS No. \_\_\_\_\_

Date \_\_\_\_\_

Item No.	Quantity	Units of Issue	Item Description	Estimated Unit Cost	Estimated Cost
1	20	Pcs.	<b>Conference Microphone</b> <ul style="list-style-type: none"> <li>• 10 inches gooseneck condenser, microphone cardioids</li> <li>• Bi-Color LED at bottom with Preamp including 3 pin XLR</li> <li>• Cardioid Polar Pattern with tailored response for speech, Integrated Desktop Base, Optional Mute Function with LED Lighting, 12" (30.5 cm) gooseneck Inline Preamp, Dual- Section gooseneck enables ease of positioning and placement options</li> <li>• XLR Cable/Connection</li> <li>• Plug and Play Solution for minimized set up times</li> </ul>	12,604.00	252,080.00
2	1	Unit	<b>Conference Camera</b> <ul style="list-style-type: none"> <li>• HD 1080P 2.1 Megapixel</li> <li>• PTZ USB Camera, 3x optional Zoom, Wide Angle 90*, Pan: 0-340*, RS- 232, RS- 422, RS- 485</li> <li>• IR Remote Control</li> </ul>	14,363.50	14,363.50
3	1	Pc	<b>Wireless Lavalier Microphone</b> <ul style="list-style-type: none"> <li>• Acoustic Principle: Permanently polarized</li> <li>• Active Electronics: JFET Impedance Converter, Capsule:0.10"</li> <li>• Address Type: End</li> <li>• Frequency Range: 60Hz- 18KHz</li> <li>• Output Impedance: 3000</li> <li>• Maximum SPL: 110Dbspl</li> <li>• Maximum Output Level: 1890mV @ 1KHz, 1% THD into 1K Load</li> <li>• Sensitivity: 33.5dB re 1 volt/Pascal (21.00mV @ 94Db spl) +/- 2Db @ 1khZ</li> <li>• Equivalent Noise (A-weighted): 25dBA</li> <li>• Operating Time: 10 hours @ 2 AA batteries 1.5v</li> </ul>	29,461.85	29,461.85