ction:			ALOBS No	Date: _	
tem No.	Quantity	Units of Issue	Item Description	Estimated Unit Cost	Estimated Co.
2	1	рс.			20,400.
XXX			Rode Wireless GO II 2-Person Digital Wireless Microphone	System/Recorder	
			Specs:		
			Acoustic & Electrical Specifications		
			Acoustic Principle		
			Pre-polarised pressure transducer		
			Polar Pattern		
			Omnidirectional		
			Frequency Range		
			50Hz – 20kHz		
			Maximum SPL (Mic)		
			100 dB SPL (1kHz @ 1m) dBu		
			Maximum Input Level (3.5mm)		
			-20dBV		
			Microphone Preamp Gain		
			20dB		
			Equivalent Noise Level (A-Weighted)		
			22dBA		
			Power Requirements		
			In-built rechargeable lithiumion battery charged via USB 5V, 0.3	SA	
			Operating Time		
			Up to 7 hours		
			Analog Inputs		
			3.5mm TRS (lavalier microphone input)		
			Analog Outputs		
			3.5mm TRS		
			Transmission Range		
			200m (line of sight)		
			Computer Connectivity	*	
			USB Type-C		
			OS Requirements		
			macOS 10.11 above Windows 7 and above		
			100 dB SPL (1kHz @ 1m) dBu		
			Maximum Input Level (3.5mm)		
			-20dBV		
			Microphone Preamp Gain		
			20dB		
			Equivalent Noise Level (A-Weighted)		
			22dBA		
	1		Power Requirements	, A	
			In-built rechargeable lithiumion battery charged via USB 5V, 0.3	DA	
			Operating Time		
			Up to 7 hours		
			Analog Inputs		00 440 95
	1		3.5mm TRS (lavalier microphone input)		20, 400,00

ia.