



Standard Form Number: SF-GOOD-58  
Revised on: May 24, 2004  
Standard Form Title: Purchase Order

PROJECT REFERENCE NO. 21-0245  
P.R No. 2021-0508

**PURCHASE ORDER**  
**OFFICE OF THE PROVINCIAL AGRICULTURIST - CROPS DIVISION/RICE SECTION**

Agency / Requisitioning Office

PO 007-15

|                |  |                            |
|----------------|--|----------------------------|
| Supplier       | <b>AGRIMACH CG CORPORATION</b>   | D.O. No. P.O. NO. 2022-056 |
| Address        | Door 1, SCI Commercial Building, Libertad Extension<br>Taculing, Bacolod City, Negros Occidental | Date : <b>FEB 22 2022</b>  |
| E-mail Address |  | Mode of                    |
| Telephone No.  | <b>9024836654</b>  | Procurement :              |
| TIN            | <b>007 - 213 - 684 - 000</b>   | <b>PUBLIC BIDDING</b>      |

Gentlemen/Mesdames:  
Please furnish this Office the following articles subject to the terms and conditions contained herein:

|                     |  |               |  |
|---------------------|--|---------------|--|
| Place of Delivery : | <b>ON SITE</b>                                     | Delivery Term | <b>Please read at the back thereof</b> |
| Address             | <b>Talibon, Bohol</b>                              | Payment Term  | <b>upon completion of delivery</b>     |
| Delivery Period:    | <b>within 120 working days upon receipt of NTP</b> |               |  |
| Warranty Period:    | <b>1 year</b>                                      |               |  |

| ITEM | UNIT | DESCRIPTION  | QTY. | UNIT COST | AMOUNT       |
|------|------|--|------|-----------|--------------|
| 1    | UNIT | Combine Rice Harvester 35 HP<br>Min. dimension: Length: 4120 mm, Width: 1850 mm, Height: 2150 mm<br>Min. weight: 1550 kg<br>Engine<br>Engine Type: Water-cooled, 4-cycle, 3-Cylinder, Vertical Diesel Engine (with Turbocharger)<br>Min. displacement: 1.123L<br>Min. output/rotation speed: 24.5 (33.3) / 3000 kW(PS)/rpm<br>Min. Fuel Tank Capacity: 60L<br>Travel Section<br>Crawler: Width x Ground Contact Length<br>400x1330 mm; Center Distance: 940 mm; Average Ground Pressure: 14.3 (0.146) kPa(kgf/cm <sup>2</sup> ); Minimum Ground Clearance: 300 mm<br>Speed shift system: Hydrostatic Variable Speed (HST)<br>Travel Speed: Forward: Low: 0-0.70 m/s<br>Backward: High: 0-1.10 m/s<br>Turning system: Clutch and Break<br>Reaper Section<br>Reel: Diameter x Width: 800 x 1420;<br>Up/Down Control: Hydraulic System<br>Gathering length: 1600 mm<br>Cutter Bar Length: 1448 mm<br>Thresher Section<br>Threshing System: Axial Flow System(Threshing Tooth System)<br>Threshing Cylinder: Diameter x Length: 545 x 1520 | 1    | 1,295,000 | 1,295,000.00 |